



Leistungsniveau

- | AFNOR: NF E 48-603 HM
- | AFNOR: NF E 48-690
- | AFNOR: NF E 48-691
- | CINCINNATI: MACHINE P-70 (ISO 46)
- | DENISON: HF-2 HLP
- | DIN: 51524 Part 2
- | EATON VICKERS: I-286-S
- | EATON VICKERS: M-2950-S
- | ISO: 11158, HM
- | ISO: 6743-4, HM

HYDRO HLP HM 46

A mineral oil, specifically designed to meet the requirements of most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion and anti-foam additives.



Anwendungen

This oil is specifically designed to satisfy the requirements of the manufacturers of hydraulic systems where the highest demands are made concerning high pressure, temperatures or speeds. It is recommended for the hydraulic systems of the following types : Vickers, Gerotor, Gresen, HPM, Denison, Cessna, Hydreco and Worthington. It is also suitable for the lubrication of workshop equipment, reducing gears, bearings, compressed air systems and air screw compressors.

Merkmale

	Unit	Average Value
Dichte bei 15 °C	g/ml	0.872
Viskosität 40 °C	mm ² /s	46.0
Viskosität 100 °C	mm ² /s	6.97
Viskositätsindex		110
Flammpunkt COC	°C	220
Fließpunkt	°C	-30
Säuregehalt	mgKOH/g	0.40
Gehalt an Sulfatasche	%	0.06

Packung



12x1L 3x5L 20L 60L 210L IBC