



Offiziell freigegeben

VW 504.00/507.00

Leistungsniveau

ACEA: C3
API: SP
VW: 504.00/507.00
MB: 229.31/229.51/229.52
BMW: Longlife-04
Porsche: C30
Opel: OV0401547

SYNTH-PRO 5W30

A fuel economy, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- | a lower fuel consumption
- | LOW SAPS content
- | suitable for modern catalyts
- | a fast cold start
- | a safe lubrication film at high temperatures
- | extended oil drain intervals
- | a very good detergency and dispersion
- | a very strong protection against wear, corrosion and foaming



Anwendungen

This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.

Merkmale

	Unit	Average Value
Dichte bei 15 °C	kg/l	0,851
Viskosität 40 °C	mm ² /s	69,20
Viskosität 100 °C	mm ² /s	12,00
Viskosität -30 °C	mPas	5950
Viskositätsindex		171
Flammpunkt COC	°C	230
Fließpunkt	°C	-42
Total Base Number	mgKOH/g	6,7
Gehalt an Sulfatasche	%	0,67

Packung



12x1L 4x4L 3x5L 20L 60L 210L IBC